VC60B⁺ Insulation Tester

Features:

- An accurate, reliable and easy-to-use insulation tester
- Large LCD display, easy to read
- Strong anti-magnetic and anti-jamming function
- Full function protection, anti high voltage circuit design
- Unit symbol display, easy to use
- High voltage and short circuit input alarm



Specifications:

	Basic function	Range	Basic accuracy	Resolution
Insulation resistance	250V±10% test voltage	0~200ΜΩ	±(4.0%+2)	100kΩ
	500V±10% test voltage	0~200ΜΩ		100kΩ
	1000V±10% test voltage	0~2GΩ		1ΜΩ
Resistance		0~2kΩ	±(1.0%+5)	1Ω
DCV		0~1000V		1V
ACV		0~750V	±(1.5%+5)	1V

Special function	VC60B⁺	
Continuity alarm	Less than 30Ω±10Ω	
Low battery indication	Less than approx.7.5V	
Data hold	$\sqrt{}$	
LCD backlight	Approx.10Sec.	
Function protection	√	
Input impedance	1ΜΩ	
Sampling rate	3 times/Sec.	
AC frequency response	50-200Hz	
Operation mode	Manual range	
Max.display	1999	
LCD size	75 x 52mm	
Power source	1.5V AA battery x6pcs, or external DC 9V power source	
Power consumption	Quiescent current approx.3mA	

General

Color	Dark gray-yellow
Weight	580g (including battery)
Meter size	176 (L) x116 (W) x63 (D) mm
Standard accessory	Test lead, shoulder strap, battery, operation manual
Packing	Gift box
Master carton packing	20pcs
Master carton size	37*35.5*42.8CM
Master carton weight	17.1KG