

NGS Total-Lube # 911



Our superior grade synthetic lubricant/ sealant is designed specifically for worn valves with minor leakage problems.

DESCRIPTION

NGS Total-Lube #911 provides an insoluble film of lubricant to protect seal faces and reduce torque requirements. Microscopic particles of PTFE will seal minor scratches to sealing surfaces and shallow corrosion pits up to 0.010". It is designed specifically as an all-purpose seat lubricant/ sealant to extend the maintenance interval in severe and critical service valves. #911 is insoluble in water, oil, natural gas, related by-products and suitable for use in sour service valves.

Total-lube #911 is recommended for use in ball, gate, and plug valves as well as orifice fittings. Use this product at refineries, wellheads, pump or compressor stations and in gas distribution systems.

Custom stick sizes are available by special request and are subject to minimum order quantities.



Product Specification

Base Oil	Synthetic
Colour	White
Drop Point	None
Texture	Tacky
Pressure	10,000 PSI
ASTM Penetration	170 – 250
Compatibility	Excellent
Solvent Resistance	Excellent
Special Additives	PTFE
Particle Size	Micronized
Composition	Semi-liquid
Temperature Range	- 29°C to + 232°C - 20°F to + 450°F

Order Details

Ordering Size	Part No.
'B' Stick - 3/8" x 1-1/2" - 72/Box	S-TL-72B
'J' Stick - 1-3/8" x 8-1/2" - 16/Box	S-TL-16J
11 Ounce Cartridge - 1 Single	S-TL-HG
15 Ounce Cartridge - 1 Single	S-TL-SG
11 Ounce Cartridges - 16/Case	S-TL-HGC
15 Ounce Cartridges - 12/Case	S-TL-SGC
10 Pound Can	S-TL-10P
40 Pound Pail	S-TL-40P
120 Pound Drum	S-TL-120D
400 Pound Drum	S-TL-400D

کد ملی کالا : 0814500970940018