



EN:61010-1

EN:61326-1



■ UT583



■ UT585

### SPECIFICATIONS

Specifications	Range	Best Accuracy			
		UT583	UT585		
<b>Model</b>					
RCD Measurement	Range Select	Rated Operating Current	Trip Time		
	× 1/2	10mA/20mA/30mA/100mA/300mA/500mA	1000mS	✓	✓
	× 1	10mA/20mA/30mA/100mA/300mA/500mA	1000mS	✓	✓
	× 2	10mA/20mA/30mA/100mA/300mA	1000mS	✓	✓
	× 5	10mA/20mA/30mA/100mA	200mS	✓	✓
	AUTO RAMP	10mA/20mA/30mA/100mA/300mA/500mA	300mS	✓	✓
	Trip Current Accuracy			±(2%+8)	±(2%+8)
	Trip Time Accuracy			±(1%+3)	±(1%+3)
	Trip Time Resolution	1mS		✓	✓
	Operational Voltage(Freq.)	230V (50Hz)		±10%	±10%
AC Voltage (V) (Freq.)	0V~440V (45~65Hz)		±(3%+5)	±(3%+5)	
<b>Features</b>					
Display Count			1000	1000	
Auto Power Off			✓	✓	
Low Battery Indication			✓	✓	
Data Hold			✓	✓	
LCD Backlight			✓	✓	
Contact Voltage Automatic Detection			✓	✓	
Over-Temperature Detection			✓	✓	
Instrumentation Devices			✓	✓	
Automatic Test			✓	✓	
Connections Check Function	Lamps Indication		✓	✓	
FUSE Security			✓	✓	

### GENERAL CHARACTERISTICS

Power	1.5V Alkaline Batteries (LR6) × 8
LCD Size	125mm × 37mm
Product Color	Red and Grey
Product Net Weight	1000g
Product Size	210mm × 175mm × 90mm
Standard Accessories	Batteries, Test Lead
Standard Individual Packing	Gift Box, Tool Box, English Manual
Standard Quantity Per Carton	4 PCs
Standard Carton Measurement	510mm × 330mm × 330mm (0.056CBM Per Standard Carton)
Standard Carton Gross Weight	15Kg