

TECHNICAL DATA

Fluke 2042 Cable locator



Key features

- For all applications (live or dead cables) without additional instruments
- Set includes a transmitter and a receiver
- Proven digitally coded sender signal guarantees clear signal identification
- Transmitter with LC-display for transmitting level, transmitting code and external voltage
- Receiver with a backlit LC-display for level of receiving signal, code of receiving signal and live voltage indication
- Automatic or manual adjustment of receiving signal sensitivity
- Acoustical receiving signal switchable
- Auto-Power-Off
- Additional torch lamp function for working in dark environments
- Additional transmitters are available for extension of to distinguish between several signals

Safety Conformance

All inputs of the Fluke 2042 is protected to EN61010-1 CAT III 300V rating.

Product overview: Fluke 2042 Cable locator

The multipurpose solution to cable location

The Fluke 2042 is a professional general purpose cable locator. It is ideal for tracing cables in walls and underground,

locating fuses/breakers on final circuits and locating interruptions and short-circuits in cables and electrical floor heating systems. It can also be used for tracing metallic water and heating pipes. The unit is supplied as a complete kit comprising of a transmitter and receiver in a purpose-made carry case. The receiver also incorporates a torch function for working in dimly lit locations.

Specifications: Fluke 2042 Cable locator

Technical Specifications		
Voltage measurement range	Transmier	12 V, 50 V, 120 V, 230 V, 400 V
Frequency range	Transmier	0 - 60 Hz
Output signal	Transmier	125 kHz
Voltage	Transmier	Up to 400 V AC/DC
Tracing depth cable location	Receiver	0 - 2.5 m wall/underground cables
Main voltage detection	Receiver	0 - 0.4 m
Environmental specifications		
Operating temperature	Transmier	0 to 40°C
	Receiver	0 to 40°C
Storage temperature	Transmier	-20°C to +60°C
	Receiver	-20°C to +60°C
Humidity (without condensation)	Transmier	Max. 80% relative
	Receiver	Max. 80% relative
Operating altitude	Transmier	Up to 2000 m
	Receiver	Up to 2000 m
Safety specifications		
Electrical safety	EN 61010-1	
Overvoltage category	Cat. III 300 V	
Mechanical and general specifications		
Size	Transmier	190 x 85 x 50 mm
	Receiver	250 x 65 x 45mm
Weight	Transmier	0.45 kg
	Receiver	0.36 kg
Baeries	Transmier	6 pc Baeries 1.5V
	Receiver	1 pc Baery 9V
Warranty	2 years	



Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2025 Fluke Corporation.
Specifications subject to change without notice.
02/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**