


# NGS Duct Sealing Compound Paste



Sealing electrical conduit openings and joints Sealing against water and dirt in electrical pot heads, against water infiltration terminal boxes, electrical bushings, and more

Sealing around steel conduits where they enter an Dampening panel noise and vibration in switch gear exposed junction



Characteristic	Product Name	Packaging
<b>Base:</b> Non-drying synthetic polymers & oils <b>Color:</b> Gray <b>Application Temp:</b> 25 to 120 °F (-4 to 49 °C) <b>Operating Temp:</b> -30 to 175 °F (-34 to 80 °C) <b>Dielectric Strength:</b> Smoke Developed - 10 100 volts/mil (ASTM D149-64) <b>Flame Resistant:</b> Flame Spread - 5	NGS Duct Sealing Compound 	1200 gr

## Application

Excellent resistance to water, alcohols, mild acids

Excellent aging characteristics - will not dry out over

Duct Seal In 1200 gr Package for sealing around electrical service entries, junction boxes and other devices where weather-proofing is critical.

- Will stay soft and pliable for several years and has an excellent shelf life
- It is chemically inert, inhibiting no chemical activity and is nontoxic.
- Contains no asbestos or mineral fibers and no mineral oil which can shorten the effective life of the product.
- Will not damage wire covers, glass, wood, painted surfaces, plastics or other materials it may contact.