

NGS Valve Flush



NGS Valve Flush is very effective in cleaning out hardened sealants and lubricants that contain solids and/or fillers in all types of valves. NGS Valve Flush does not contain acid, caustic, solvent, or solids. NGS Valve Flush is a synthetic and Vegetable oil based .that is bio- degradable, safe and non-hazardous. It is compatible with all valve lubricants and sealants.

Characteristic	Product	Packaging																
<ul style="list-style-type: none">Compatible with most valve lubricants and sealantsRemoves rust and corrosionDo not use in oxygen serviceTemperature range: 0° to 400°F <table border="1"><thead><tr><th>PROPERTY</th><th>UNIT</th><th>TEST METHOD</th><th>ACCEPTANCE CRITERIA</th></tr></thead><tbody><tr><td>Relative density</td><td>-</td><td>ASTM D-4052</td><td>0.975 (H2O = 1)</td></tr><tr><td>VISCOSITY@40°C</td><td>CST</td><td>ASTM D445</td><td>10</td></tr><tr><td>FLASH POINT</td><td>° C</td><td>ASTM D93</td><td>>300</td></tr></tbody></table>	PROPERTY	UNIT	TEST METHOD	ACCEPTANCE CRITERIA	Relative density	-	ASTM D-4052	0.975 (H2O = 1)	VISCOSITY@40°C	CST	ASTM D445	10	FLASH POINT	° C	ASTM D93	>300	NGS Valve flush	CAN 1000 ml 4000 ml 20000ml
PROPERTY	UNIT	TEST METHOD	ACCEPTANCE CRITERIA															
Relative density	-	ASTM D-4052	0.975 (H2O = 1)															
VISCOSITY@40°C	CST	ASTM D445	10															
FLASH POINT	° C	ASTM D93	>300															

Application
Cleaning of seat of ball valve
Good corrosion protection

www.ngschemicals.com

Manufactured by N.G.S company Tel :041-34252985