



EN:61326-1

NEW



■ UT331



■ UT332

SPECIFICATIONS

 ROHS
 MAX
 MIN
 USB

Specifications	Range	Best Accuracy		
		UT331	UT332	
Model		UT331	UT332	
Temperature	Range	-20°C ~60°C (-4°F~140°F)	✓	✓
	Accuracy	0°C ~40°C	±0.5°C	±0.5°C
		-20°C ~0°C	±1°C	±1°C
		40°C ~60°C	±1°C	±1°C
Resolution	0.1°C/0.1°F	✓	✓	
Humidity	Range	0%RH~100%RH	✓	✓
	Accuracy	10%RH~90%RH	±3.5%RH	±2.5%RH
		<10%RH or >90%RH	±5%RH	±5%RH
		Resolution	0.1%RH	✓
Features				
°C/°F Selection		✓	✓	
Response Time	Around 10 Seconds	✓	✓	
Humidity Offset Settings		✓	✓	
Temperature Offset Settings		✓	✓	
Dew Point Offset Settings		✓	✓	
Auto Power Off		✓	✓	
Power Saving Mode			✓	
Data Hold		✓	✓	
MAX/MIN		✓	✓	
Data Logging		100	100	
Data Recall		✓	✓	
USB Interface		✓	✓	
Auto Record Time Setup		✓	✓	
LCD Backlight		✓	✓	

GENERAL CHARACTERISTICS

Power	1.5V Alkaline Batteries (LR03) × 4
LCD Size	26.5mm × 35.5mm
Product Color	Red and Grey
Product Net Weight	130g
Product Size	185mm × 54.8mm × 33.8mm
Standard Accessories	Batteries, USB Interface Cable, PC Software CD
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	555mm × 430mm × 288mm
Standard Carton Gross Weight	15.9Kg