

Page 1 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 20.08.2018 / 0010
Replacing version dated / version: 30.08.2017 / 0009
Valid from: 20.08.2018
PDF print date: 24.08.2018
Hochglanz-Antihologramm-Politur M2.01

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Hochglanz-Antihologramm-Politur M2.01

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Polish

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

GB

Koch-Chemie GmbH, Einsteinstrasse 42, 59423 Unna, Germany
Phone:+49 (0) 2303/9 86 70 - 0, Fax:+49 (0) 2303/9 86 70 - 26
KCU@KOCH-CHEMIE.de, www.KOCH-CHEMIE.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:
+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)
+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (KCC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Avoid long lasting or intensive contact with skin.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 20.08.2018 / 0010
Replacing version dated / version: 30.08.2017 / 0009
Valid from: 20.08.2018
PDF print date: 24.08.2018
Hochglanz-Antihologramm-Politur M2.01

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119457273-39-XXXX
Index	---
EINECS, ELINCS, NLP	918-481-9 (REACH-IT List-No.)
CAS	(64742-48-9)
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Keep Data Sheet available.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting.

Call doctor immediately - have Data Sheet available.

Danger of aspiration

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritant effect to damaged skin.

With long-term contact:

Irritation of the eyes

Irritation of the skin.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 20.08.2018 / 0010
Replacing version dated / version: 30.08.2017 / 0009
Valid from: 20.08.2018
PDF print date: 24.08.2018
Hochglanz-Antihologramm-Politur M2.01

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Fume

Toxic pyrolysis products.

Hydrocarbons

5.3 Advice for firefighters

According to size of fire

Protective respirator with independent air supply.

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

Ensure sufficient supply of air.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Keep away from sources of ignition - Do not smoke.

Observe directions on label and instructions for use.

Ensure sufficient ventilation.

Take measures against electrostatic charging, if appropriate.

Unsuitable material:

Materials sensitive to solvents

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Protect against moisture and store closed.

Store cool.

7.3 Specific end use(s)

No information available at present.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 20.08.2018 / 0010
Replacing version dated / version: 30.08.2017 / 0009
Valid from: 20.08.2018
PDF print date: 24.08.2018
Hochglanz-Antihologramm-Politur M2.01

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):
800 mg/m³

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:10-20
WEL-TWA: 800 mg/m ³	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) 	
BMGV: ---	Other information: (WEL acc. to RCP-method, EH40)	

Chemical Name	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:10-20
OELV-8h: 100 ppm (573 mg/m ³) (White Spirit)	OELV-15min: 125 ppm (720 mg/m ³) (White Spirit)	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Hydrocarbons 2/a (81 03 581) - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Compur - KITA-187 S (551 174) 	
BLV: ---	Other information: ---	

Chemical Name	Aluminium oxide	Content %:
WEL-TWA: 10 mg/m ³ (total inhal. dust), 4 mg/m ³ (resp. dust) (aluminium oxides)	WEL-STEL: ---	---
Monitoring procedures:	---	
BMGV: ---	Other information: ---	

Chemical Name	Aluminium oxide	Content %:
OELV-8h: 4 mg/m ³ (respirable dust), 10 mg/m ³ (total inhalable dust) (Aluminium oxides)	OELV-15min: ---	---
Monitoring procedures:	---	
BLV: ---	Other information: ---	

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m ³ (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031) 	
BMGV: ---	Other information: ---	

Chemical Name	Oil mist, mineral	Content %:
OELV-8h: 5 mg/m ³ (Mineral oil, pure, highly & severely refined (inhalable))	OELV-15min: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031) 	
BLV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable

Page 5 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.08.2018 / 0010
 Replacing version dated / version: 30.08.2017 / 0009
 Valid from: 20.08.2018
 PDF print date: 24.08.2018
 Hochglanz-Antihologramm-Politur M2.01

Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BLV = Biological limit value | Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

M OELV-8h = Occupational Exposure Limit Value - 8 h (8-hour reference period as a time-weighted average)

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU).

[9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24). | OELV-ST = Occupational Exposure Limit Value - Short-term (15-minute reference period)

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU).

[8] = Short-term exposure limit value in relation to a reference period of 1 minute. (S.L.424.24), [9] = Inhalable fraction (S.L.424.24), [10] = Respirable fraction (S.L.424.24) | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Skin = Possibility of a significant uptake through the skin.

[11] = When selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds. (S.L.424.24), [12] = The mist is defined as the thoracic fraction.

(S.L.424.24), [13] = Established in accordance with the Annex to Directive 91/322/EEC. (S.L.424.24), [14] = During exposure monitoring for mercury and its divalent inorganic compounds, account should be taken of relevant biological monitoring techniques that complement the OELV. (S.L.424.24)

8.2 Exposure controls

Aluminium oxide						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	20	mg/l	
Industrial	Human - inhalation	Long term	DNEL	3	mg/m ³	
Commercial	Human - inhalation	Long term	DNEL	3	mg/m ³	
Consumer	Human - oral	Long term	DNEL	6,22	mg/kg bw/day	

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Protective gloves in butyl rubber (EN 374).

Page 6 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 20.08.2018 / 0010
Replacing version dated / version: 30.08.2017 / 0009
Valid from: 20.08.2018
PDF print date: 24.08.2018
Hochglanz-Antihologramm-Politur M2.01

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

> 120

Preventative skin protection advisable.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask

Filter AP1 (EN 14387)

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Viscous, Liquid
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	>93 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,01 g/cm ³ (20°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	>20,5 mm ² /s (40°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
--------------	----------------

Page 7 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.08.2018 / 0010
 Replacing version dated / version: 30.08.2017 / 0009
 Valid from: 20.08.2018
 PDF print date: 24.08.2018
 Hochglanz-Antihologramm-Politur M2.01

Fat solubility / solvent: Not determined
 Conductivity: Not determined
 Surface tension: Not determined
 Solvents content: 12 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Stable when handled and stored correctly.

10.5 Incompatible materials

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

None known

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Hochglanz-Antihologramm-Politur M2.01

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m ³ /8 h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.

Page 8 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.08.2018 / 0010
 Replacing version dated / version: 30.08.2017 / 0009
 Valid from: 20.08.2018
 PDF print date: 24.08.2018
 Hochglanz-Antihologramm-Politur M2.01

Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:					OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 421 (Reproduction/Developmental Toxicity Screening Test)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	No indications of such an effect., Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						unconsciousness, headaches, dizziness, vomiting, nausea

Aluminium oxide						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	NOAEL	30	mg/kg	Rat		Analogous conclusion
Acute toxicity, by inhalation:	NOAEC	70	mg/m3	Rat		subchronic
Acute toxicity, by inhalation:	LC50	7,6	mg/l/4h	Rat		Aerosol, Maximum achievable concentration.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitizing
Germ cell mutagenicity:					in vivo	Negative, Analogous conclusion
Symptoms:						constipation
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	70	mg/m3	Rat		Lung damage

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 20.08.2018 / 0010

Replacing version dated / version: 30.08.2017 / 0009

Valid from: 20.08.2018

PDF print date: 24.08.2018

Hochglanz-Antihologramm-Politur M2.01

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Hochglanz-Antihologramm-Politur M2.01

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOELR	28d	0,1	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	21d	0,18	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErL50	72h	>1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Pow		5,5-7,2				
12.4. Mobility in soil:	Log Koc		>3				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Water solubility:			~10	mg/l			Slight

Aluminium oxide

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	218,6	mg/l	Pimephales promelas		

Page 10 of 13
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 20.08.2018 / 0010
 Replacing version dated / version: 30.08.2017 / 0009
 Valid from: 20.08.2018
 PDF print date: 24.08.2018
 Hochglanz-Antihologramm-Politur M2.01

12.1. Toxicity to daphnia:	NOEC/NOEL	48h	>0,135	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	EC50		>100	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50		>100	mg/l	Selenastrum capricornutum		
12.1. Toxicity to algae:	NOEC/NOEL	72h	>=0,052	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

12 01 09 machining emulsions and solutions free of halogens

12 01 20 spent grinding bodies and grinding materials containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Page 11 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 20.08.2018 / 0010
Replacing version dated / version: 30.08.2017 / 0009
Valid from: 20.08.2018
PDF print date: 24.08.2018
Hochglanz-Antihologramm-Politur M2.01

Marine Pollutant: n.a
14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:
14.3. Transport hazard class(es): n.a.
14.4. Packing group: n.a.
14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 12 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 8

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

Any abbreviations and acronyms used in this document:

AC Article Categories
acc., acc. to according, according to
ACGIH American Conference of Governmental Industrial Hygienists
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOEL Acceptable Operator Exposure Level
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BCF Bioconcentration factor
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)
BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)
BMGV Biological monitoring guidance value (EH40, UK)
BOD Biochemical oxygen demand

Page 12 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 20.08.2018 / 0010
Replacing version dated / version: 30.08.2017 / 0009
Valid from: 20.08.2018
PDF print date: 24.08.2018
Hochglanz-Antihologramm-Politur M2.01

BSEF Bromine Science and Environmental Forum
bw body weight
CAS Chemical Abstracts Service
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC Collaborative International Pesticides Analytical Council
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
COD Chemical oxygen demand
CTFA Cosmetic, Toiletry, and Fragrance Association
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
DOC Dissolved organic carbon
DT50 Dwell Time - 50% reduction of start concentration
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEA European Economic Area
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ERC Environmental Release Categories
ES Exposure scenario
etc. et cetera
EU European Union
EWC European Waste Catalogue
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
HET-CAM Hen's Egg Test - Chorionallantoic Membrane
HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container
IBC (Code) International Bulk Chemical (Code)
IC Inhibitory concentration
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low
LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAEC No Observed Adverse Effective Concentration

Page 13 of 13
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 20.08.2018 / 0010
Replacing version dated / version: 30.08.2017 / 0009
Valid from: 20.08.2018
PDF print date: 24.08.2018
Hochglanz-Antihologramm-Politur M2.01

NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level
ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organic
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene
PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship
SU Sector of use
SVHC Substances of Very High Concern
Tel. Telephone
ThOD Theoretical oxygen demand
TOC Total organic carbon
TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.