



EN:61326-1

NEW



■ UT341

SPECIFICATIONS

Specifications	Range	Best Accuracy	
Model		UT341	UT342
Iron Matrix Measure	0 μ m~55 μ m 56 μ m~1000 μ m	\pm 3dgt \pm (3.0%+1dgt)	\pm 3dgt \pm (3.0%+1dgt)
Aluminum Matrix Measure	0 μ m~55 μ m 56 μ m~1000 μ m	\pm 3dgt \pm (3.0%+1dgt)	\pm 3dgt \pm (3.0%+1dgt)
Resolution	1 μ m	✓	✓
Features			
Display Count		9999	9999
Auto Power Off		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
MAX/MIN		✓	✓
Data Logging		2000	2000
LCD Backlight		✓	✓
Measurement Mode	Continuous or Single Measurement	✓	✓
Key Mis-press Buzzer		✓	✓



■ UT342

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery (6LF22)
LCD Size	22mm × 22mm
Product Color	Red and Grey
Product Net Weight	144.2g
Product Size	153mm × 110mm × 40mm
Standard Accessories	UT341 -Battery, Standard Membrane Slice, Iron Matrix Slice, Carrying Bag UT342 -Battery, Standard Membrane Slice, Iron Matrix Slice, Aluminum Matrix Slice, Carrying Bag
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	530mm × 485mm × 320mm (0.082 CBM Per Standard Carton)
Standard Carton Gross Weight	9.5 Kg