

# 223400121340

## Modular contactor








### Technical description:

Modular contactor, 25 A, 4 pole, NO, 25 A, AgNi, AC/DC coil, 12 V, operating from 9.6 to 13.2 V (AC)/(DC), rated power 2 VA (AC) / 2.2 W (DC), holding voltage 4.8 V (AC)/(DC), must drop-out voltage 1.2 V (AC)/(DC), option: Auto-On-Off selector + mechanical indicator + LED, ambient temperature from -25 to +50 °C

*This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.*

[BROWSE PRODUCT PAGE](#)

### Technical Features:

<b>Ambient temperature range:</b>	-25...50 °C
<b>Commercial description:</b>	Modular contactor 25 A - 4 contacts, 35mm width and a NO contact gap e 3 mm, double break. Type 22.34 complies with EN 61095: 2009
<b>Contact configuration:</b>	4 pole, NO
<b>Dimensions:</b>	35x84x56.5 mm
<b>Electrical life:</b>	150000 cycles
<b>Insulation coil/contacts:</b>	6 kV
<b>Nominal voltage:</b>	12 V
<b>Operating range ac:</b>	9.6...13.2 V
<b>Operating range dc:</b>	9.6...13.2 V
<b>Rated contact voltage:</b>	250 V AC
<b>Rated current (contacts):</b>	25 A
<b>Supply:</b>	AC/DC
<b>Certifications and quality approvals (according to type):</b>	    

The information, technical details, data and features contained in this document are subject to change or modification at any time. It is for information purposes only and does not form the basis of a contract.

### Need more information?

[Contact our sales](#) [Find a dealer](#)