



EN:61326-1

NEW

■ UT313

SPECIFICATIONS

Specifications	Range	Best Accuracy	
Model		UT313	UT315
Acceleration(Freq.)	0.1~199.9m/s ² (10Hz ~ 10KHz)	±(5% + 2)	±(5% + 2)
Velocity(Freq.)	0.01~19.99cm/s(10Hz ~ 1KHz)	±(5% + 2)	±(5% + 2)
Displacement(Freq.)	0.001~1.999mm(10Hz ~ 500Hz)	±(5% + 2)	±(5% + 2)
Features			
Display Count		1999	1999
Auto Power Off		✓	✓
Low Battery Indication	≤7.0V	✓	✓
Data Hold		✓	✓
MAX Mode		✓	✓
Data Logging		1999	1999
Data Recall		✓	✓
USB Interface		✓	✓
LCD Backlight		✓	✓



■ UT315

GENERAL CHARACTERISTICS

Power	9V Alkaline Battery (6LF22)
LCD Size	57mm × 37mm
Product Color	Red and Grey
Product Net Weight	365g
Product Size	166mm × 80mm × 30mm
Standard Accessories	UT313 -Battery ,Magnet Pedestal,Long Probe,Short Probe,Connection Screw,Carrying Bag UT315 -Battery,USB Interface Cable,PC Software CD,Magnet Pedestal,Long Probe,Short Probe,Connection Screw,Carrying Bag
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	530mm × 420mm × 365mm (0.081 CBM Per Standard Carton)
Standard Carton Gross Weight	24 Kg