

COPPER GRADE ANTI-SEIZE

Performs to 1093°C



COPPER GRADE ANTI-SEIZE

Copper Grade Anti-Seize is produced from fine metallic particles. The properties are similar to Regular Anti-Seize but anti-galvanic properties are not as great.

Characteristic	Product Name	Packaging
BASIC COMPOSITION: fine metallic particles COLOR: METALLIC COPPER TEMPERATURE: -53 TO 1093°C. NLGI GRADE: 1 SPECIFIC GRAVITY: 1.2 DROP POINT: 193.33°C FLASH POINT: C.O.C. 260°C PENETRATION: 270 +-20 PARTICLE SIZE: 1 MIL. MAXIMUM COEFFICIENT OF FRICTION: 0.07* * SHELL 4 BALL METHOD.	COPPER -Anti-Seize	250 gr. CAN 500 gr. CAN 1000 gr . CAN
Application		
<p>Can be used as a lubricant, a sealer, a break in lubricant, a tapping compound on plastics as well as metals. Surface need not be cleaned before application unless grit or low quality oil/grease is present and ultimate performance is required. The reduction in assembly friction increases torque tension by about 20%. Use on threaded parts, bushings, gears, valve stems, chain sprockets, levers, hinges, pivots, rollers, heat exchanger or manifold bolts, or as a gasket release agent, etc. NOTE: This product is not recommended for pure oxygen systems.</p>		