

Heavy Duty Slugging Wrenches

Carl Walter Heavy Duty Slugging Wren



- ✦ High quality forged steel
- ✦ Made of chrome-vanadium steel
- ✦ Phosphate protected against corrosion
- ✦ The optimum thickness of production
- ✦ Be appropriate for heavy screws
- ✦ Ruhr basin, steel processing technology
- ✦ High German technology, long-lasting
- ✦ Carl Walter made in Germany
- ✦ Distributor By Parla Tech in Iran.

➤ Tulex extra Heavy Duty Slugging / Striking Wrenches are designed for use with hammers where impact or shock loading is required for loosening of frozen and rusty nuts and bolts. These slugging wrenches are duly forged from superior grade chrome vanadium steel. The blanks are duly machined with the wrench openings broached to tolerance as per federal specifications. These slugging wrenches undergo a heat treatment process including stress relieving before undergoing short blasting and surface finish operations.

➤ Slagging Ring Wrench

Model No	Across Flat	Head Dia (A)	Head Depth (M)	Lenght (L)	Weight
----------	-------------	--------------	----------------	------------	--------

#	mm	mm	mm	mm	Kg
SG1124	24	43	15	165	0,4
SG1127	27	46	16	180	0,4
SG1130	30	52	17	190	0,5
SG1132	32	52	17	190	0,5
SG1136	36	58	18	205	0,5
SG1141	41	66	20	230	0,8
SG1146	46	74	22	240	1,0
SG1150	50	80	24	255	1,1
SG1155	55	86	25	270	1,5
SG1160	60	93	26	280	1,8
SG1165	65	102	30	300	2,2
SG1170	70	110	33	330	3,3
SG1175	75	110	33	330	3,3
SG1180	80	126	36	360	4,5
SG1185	85	126	36	360	4,5
SG1190	90	142	40	390	5,5
SG1195	95	142	40	420	5,3
SG11100	100	155	45	420	6,5



➤ Open Jaw Slugging Wrench

Model No	Across Flat	Head Dia (A)	Head Depth (M)	Length (L)	Weight
----------	-------------	--------------	----------------	------------	--------

	mm	mm	mm	mm	Kg
SG9524	24	56	16	180	0,4
SG9527	27	56	16	180	0,4
SG9530	30	62	17	190	0,5
SG9532	32	62	17	190	0,5
SG9536	36	76	18	215	0,55
SG9541	41	86	19	235	0,9
SG9546	46	98	20	225	1,2
SG9550	50	105	21	275	1,5
SG9555	55	114	23	300	1,9
SG9560	60	128	25	320	2,6
SG9565	65	138	27	340	3,4
SG9570	70	154	30	375	4,4
SG9575	75	154	30	375	4,4
SG9580	80	174	34	410	6,3
SG9585	85	174	34	410	6,3
SG9590	90	194	38	445	7,3
SG9595	95	194	38	445	7,3
SG95100	100	215	44	485	12,2

