

# Polilyte Plus H VP 120 Pt100

Specification Sheet (Part/REF # 242428-1111)



Polilyte Plus Traditional pH sensor offer multiple electrical connectors and length options along with a standard mV output compatible with most transmitters and controllers.

## Product Specifications

<b>Sensor Family</b>	Polilyte Plus
<b>Parameter</b>	pH
<b>Sensor Output</b>	Traditional: mV
<b>a-length</b>	120 mm
<b>Electrical Connector</b>	VP6
<b>Measurement Principle</b>	Combination electrode; pH potential measured against reference
<b>Measuring Range</b>	pH 0 to 14
<b>Sensitivity</b>	57 to 59 mV / pH at 25 °C
<b>Zero Point</b>	0 ± 20 mV
<b>pH Glass</b>	Hamilton Type H Glass
<b>pH Glass Resistance</b>	Moderate
<b>Membrane Shape</b>	Spherical
<b>Diaphragm</b>	Single Pore
<b>Number of Diaphragms</b>	2
<b>Electrolyte</b>	Polisolve Plus
<b>Reference System</b>	Hamilton Everef-L
<b>Liquid Earth</b>	Yes
<b>Temperature Sensor</b>	Pt100
<b>Diameter</b>	12 mm
<b>Process Connection</b>	PG13,5
<b>Wetted Parts</b>	Glass FKM (Fluorocarbon Elastomer)
<b>Serial Number</b>	Yes
<b>Recommended Storage</b>	Hamilton Storage Solution or 3 M KCl
<b>Certificate</b>	Yes, with measured values in Buffer pH 4.01 and pH 7.00
<b>ATEX Approval</b>	II 1/2 G Ex ia IIC T4/T5/T6 Ga/Gb; II 1/2 D ia IIIC T x °C Da/Db
<b>IECEX Approval</b>	II 1/2 G Ex ia IIC T4/T5/T6 Ga/Gb; II 1/2 D ia IIIC T x °C Da/Db
<b>Autoclavable</b>	Yes, max. Temperature 130 °C
<b>CIP</b>	No
<b>Steam Sterilizable</b>	Yes, max. Temperature 130 °C

**Operating Temperature Range** 0 to 130 °C

---

**Sample min Conductivity** 2 µS/cm

---

**Pressure Range bar g** 0 to 16 bar (100 °C), 0 to 10 bar (130 °C)

---

Specifications are subject to change without notice

**Spec. Version B**

<https://www.hamiltoncompany.com/process-analytics/sensors/242428-1112-1>