



Max width single leaf

2,2 - 7 m (with electric lock)

Use frequency (cycles/hour)

50 - 70



- Key-protected, release device
- Extremely silent movement.
- Hydraulic lock resistant to intrusion attempts (mod. CBC - CBAC).



SAFEzone system:
400 + E045 or E145 +
SAFEcoder



GREENTech system:
400 + E045 or E145



DIMENSIONS AND TECHNICAL SPECIFICATIONS

Model	400 CBC	400 SB	400 SBS	400 CBAC	400 CBAC L	400 SBS L
Power supply voltage	220-240V~ 50/60 Hz					
Motor	Asynchronous single phase					
Max. power	220 W					
Max expressed force	6200 N (*)		7750 N (*)	6200 N (*)	4650 N (*)	7750 N (*)
Rod max speed	10 mm/s (*)		7,5 mm/s (*)	10 mm/s (*)	15 mm/s (*)	7,5 mm/s (*)
Motor-pump unit capacity	1 lpm (*)		0,75 lpm (*)	1 lpm (*)	1,5 lpm (*)	0,75 lpm (*)
Rod travel		270 mm				390 mm
Max. leaf opening angle	125°					
Operating ambient temperature	-20°C ÷ + 55°C					
Thermal protection	120°C					
Protection class	IP55					
Weight	8,6 Kg				10 kg	
Use frequency	70 cycles/hour		60 cycles/hour	70 cycles/hour	50 cycles/hour	40 cycles/hour
Max. leaf width	2.20 m	4,00 m (with electric lock)	7,00 m (with electric lock)		2.20 m	7,00 m (with electric lock)
Type of oil	FAAC HP OIL					
Mounting brackets	Rear attachment to be welded/screwed - front attachment to be welded					
Dimensions (LxDxH)	1034 x 85 x 119 mm				1277 x 85 x 119 mm	
Electronic equipment	Not included					

(*) data referred to 230V~ 50Hz.