

MULTIPLE OUTPUT LINEAR D.C. POWER SUPPLY



GPS-2303/3303/4303



Patent No: ZL 02 3 35264 . 7

FEATURES

- * 2, 3 and 4 Independent Isolated Output
- * Four "3 Digits" LED Displays
- * 0.01% Load and Line Regulation
- * Low Ripple and Noise
- * Tracking Operation and Auto Series/Parallel Operation
- * Output ON/OFF Switch
- * Output Voltage and Current Setting When Output Disable (Except GPS-2303)
- * Fan Speed Control Circuit to Minimize Fan Noise
- * Over Load and Reverse Polarity Protection
- * Optional European Jack Type Terminal

The GPS-Series is dual to quad output, 180 to 200W, linear DC power supply. Overload/reverse polarity protection and output On/Off switch keep GPS and loads safe from unexpected conditions. High regulation and low ripple/noise are maintained at 0.01% and less than 1mVrms, respectively. Cooling fan speed control minimizes fan noise according to load conditions, ensuring quiet operation. The GPS-Series is an ideal solution for lightweight, inexpensive bench-top or portable applications requiring high regulation and multiple outputs.

SPECIFICATIONS									
	GPS-4303			GPS-3303			GPS-2303		
OUTPUT MODE									
	CH1	CH2	CH3	CH4	CH1	CH2	CH3	CH1	CH2
Voltage	0 ~ 30V		2.2 ~ 5.2V	8 ~ 15V	0 ~ 30V		5V Fixed	0 ~ 30V	
Current	0 ~ 3A		1A Max.	1A Max.	0 ~ 3A		3A Max.	0 ~ 3A	
Tracking Series Voltage	0 ~ 60V		----		0 ~ 60V		----		0 ~ 60V
Tracking Parallel Current	0 ~ 6A				0 ~ 6A				0 ~ 6A
CONSTANT VOLTAGE OPERATION (CH1, CH2)									
Line Regulation	≤ 0.01% + 3mV								
Load Regulation	≤ 0.01% + 3mV (rating current ≤ 3A) ≤ 0.02% + 5mV (rating current > 3A)								
Ripple & Noise	≤ 1mVrms, 5Hz ~ 1MHz								
Recovery Time	≤ 100μS (50% Load change, Minimum load 0.5A)								
CONSTANT CURRENT OPERATION (CH1, CH2)									
Line Regulation	≤ 0.2% + 3mA								
Load Regulation	≤ 0.2% + 3mA								
Ripple & Noise	≤ 3mArms								
TRACKING OPERATION (CH1, CH2)									
Tracking Error	≤ 0.5% + 10mV of the CH1								
Series Regulation	≤ 300mV								
Load Regulation	≤ 0.01% + 3mV								
Ripple & Noise	≤ 2mVrms, 5Hz ~ 1MHz								
CH3 OPERATION (for GPS-3303/4303)									
CH3 Voltage	GPS-4303 : 2.2V ~ 5.2V, GPS-3303 : 5V Fix								
Line Regulation	≤ 5mV								
Load Regulation	≤ 15mV								
Ripple & Noise	≤ 2mVrms, 5Hz ~ 1MHz								
Current Output	GPS-4303 : 1A, GPS-3303 : 3A								
CH4 OPERATION (for GPS-4303)									
CH4 VOLTAGE	8V ~ 15V								
Line Regulation	≤ 5mV								
Load Regulation	≤ 10mV								
Ripple & Noise	≤ 2mVrms, 5Hz ~ 1MHz								
Current Output	1A								
METER									
Digital	3 digits 0.5" LED display GPS-4303/3303 Out ON Accuracy ± (0.5% rdg + 2 digits) GPS-4303/3303 Out OFF Accuracy ± (0.5% rdg + 8 digits) GPS-2303 Accuracy ± (0.5% rdg + 2 digits)								
INSULATION									
Chassis and Terminal	≥ DC 500V / 20MΩ								
Chassis and AC Cord	≥ DC 500V / 30MΩ								
POWER SOURCE									
AC 100V/120V/220V±10%, 230V(+10%~-6%), 50/60Hz									
DIMENSIONS & WEIGHT									
255(W) x 145(H) x 265(D) mm, Approx. 7 kg (GPS-4303/3303/2303)									

ORDERING INFORMATION

- GPS-4303** 4-channels, 200W D.C. Power Supply
- GPS-3303** 3-channels, 195W D.C. Power Supply
- GPS-2303** 2-channels, 180W D.C. Power Supply

ACCESSORIES :

- User manual x 1, Power cord x 1,
- GPS-4303: Test lead GTL-104 x 2, GTL-105 x 2 ; European test lead GTL-203 x 2, GTL-204 x 2, GTL-201A x 1
- GPS-3303: Test lead GTL-104 x 2, GTL-105 x 1 ; European test lead GTL-203 x 1, GTL-204 x 2, GTL-201A x 1
- GPS-2303: Test lead GTL-104 x 2 ; European test lead GTL-204 x 2, GTL-201A x 1