



IEC:1010-1
IEC:1010-2-032
IEC:61326

NEW



■ UT255A

SPECIFICATIONS



Specifications	Range	Best Accuracy		
Model		UT255A	UT255B	
Leakage Current(A)	Range	0.01mA~100.0A	±(1%+5)	±(1%+5)
		100.0A~600.0A	±(2%+5)	±(2%+5)
	Voltage(Freq.)	0V~69KV(50Hz/60Hz)	✓	✓
Features				
Display Mode	4 Digits Display LCD	✓	✓	
Jaw Capacity		33mm	33mm	
Auto Range		✓	✓	
Wireless Transmission	≤30m		✓	
Data Recall		✓	✓	
Data Logging		99	99	
Peak Value		✓	✓	
LCD Backlight		✓	✓	
Data Hold		✓	✓	
Auto Power Off	Around 15 Minutes	✓	✓	
Low Battery Indication		✓	✓	
Over-Range Display	OL	✓	✓	
Test Mode	Clamp CT, Integral Approach	✓	✓	
Sample Rate	About 2 times/second	✓	✓	



■ UT255B

GENERAL CHARACTERISTICS

Power	1.5V Alkaline Batteries (LR03)×4
LCD Size	47mm × 28.5mm
Product Color	Red and Grey
Product Net Weight	335g
Product Size	68mm × 245mm × 40mm
Standard Accessories	UT255A-Batteries,Insulation Rod ,Tool Box UT255B-Batteries,Insulation Rod,Receiver,Tool Box
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	6 PCs
Standard Carton Measurement	1030mm × 520mm × 450mm (0.241 CBM Per Standard Carton)
Standard Carton Gross Weight	40 Kg